GIPS



UWB Tag - Watch Type

Since 102.15.4 UWB

- BLE 5.0
- IPX6
- SOS alert
- Vibration, Buzzer
- 📀 Vital sign, Activity monitoring
- Message Issuance

Specifications

Mechanical & Environmental

Standard	IEEE802.15.4aBLE 5.0
Size (mm)	ø45 x 14.5 (wrist band excluded)
Weight (g)	45
Power Requirement	+5V DC-in with magnetic charging sit
Power Consumption	< 1W (Instant)
Battery Life	 ToF: 1+ Days@1Hz w/ smart sleep TDoA: 2+ Days@1Hz w/ smart sleep Battery life would change according to the screen, vital sign sensor usage
Blink Rate	0.1 ~ 20Hz (Adjustable)
Display	1.32-inch TFT screen with a resolution of 360x360
Temperature	 Operating: 0°C ~ 60°C Storage: 0°C ~ 70°C
Humidity	 40°C @ 95% Relative Humidity, Non-condensing
IP Rating	IP X6
Functions	 SOS alert Vibration Buzzer Message Smart Rest Mode Heart Rate Monitor Blood Oxygen Monitor Activity Monitor

UWB

Frequency	 Low Band: 3.5GHz ~ 6.5GHz (CH2/CH3) High Band: 6.5GHz ~ 8GHz (CH5/CH9)
Physical Rate	 110 Kbps 850 Kbps 6.8 Mbps
Channel Frequency Width	500 MHz
Working Mode	• ToF • TDoA

Friday

BLE

Frequency	2400MHz ~ 2483.5MHz
Physical Rate	 2 Mbps 1 Mbps 125 Kbps